

35W EXTERMINATOR II – model: 1035

LEDme® W Track Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

LEDme® Exterminator offers superior light output in a small, unobtrusive design. Developed for upscale residential and commercial environments.

FEATURES

- Accommodates one lens accessory and one glare control accessory
- Reflectors and LED modules can be purchased separately for alternative beam angles and color temperatures
- 365° horizontal rotation and 180° vertical aiming
- 60,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction:	Die-cast aluminum with removable front cap for easy change of lenses or accessories
Power Consumption:	35W
Light Source:	High output COB LED
Dimming:	100%-5% Electronic Low Voltage
Finish:	Powder coated Black, Platinum and White
Standards:	ETL&cETL Listed, Energy Star® rated CEC Title 24 Compliant

ORDER NUMBER

System	Beam	Color Temp	CRI	Lumens	CBCP	Finish
WTK 120V	1035N 25°	827 2700K	85	2487	8723	BK Black PT Platinum WT White
		927 2700K	90	2020	7069	
		830 3000K	85	2652	9279	
		930 3000K	90	2176	7517	
		835 3500K	85	2773	9710	
		840 4000K	85	2795	9748	
	1035F 55°	827 2700K	85	2476	3409	
		927 2700K	90	2029	2824	
		830 3000K	85	2691	3700	
		930 3000K	90	2185	3035	
		835 3500K	85	2815	3873	
		840 4000K	85	2828	3886	
WHK 277V	1035N 25°	827 2700K	85	2487	8723	
		927 2700K	90	2020	7069	
		830 3000K	85	2652	9279	
		930 3000K	90	2176	7517	
		835 3500K	85	2773	9710	
		840 4000K	85	2795	9748	
	1035F 55°	827 2700K	85	2476	3409	
		927 2700K	90	2029	2824	
		830 3000K	85	2691	3700	
		930 3000K	90	2185	3035	
		835 3500K	85	2815	3873	
		840 4000K	85	2828	3886	

FLAT LENS ACCESSORIES

Amber	LENS-20-AMB
Blue	LENS-20-BLU
Green	LENS-20-GRN
Red	LENS-20-RED
Yellow	LENS-20-YEL
UV Filter	LENS-20-UVF
Frosted	LENS-20-FR
Spread	LENS-20-SPR
Beam Elongating	LENS-20-BEL

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-20-CRL
Snoot	LENS-20-SNOOT

REFLECTORS

25°	SL-REF-BL18-N
55°	SL-REF-BL18-F

LED MODULES

2700K CRI 85	BXRC-27E4000-F-23
2700K CRI 90	BXRC-27G4000-F-23
3000K CRI 85	BXRC-30E4000-F-23
3000K CRI 90	BXRC-30G4000-F-23
3500K CRI 85	BXRC-35E4000-F-23
4000K CRI 85	BXRC-40E4000-F-23



Example: WTK-1035N-827-WT

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760