

PIXELS

Configurable LED Light Sheet

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Professional flexible light sheet creates uniform and linear illumination. Easy installation in any minimal size application with no heat sink needed.

FEATURES

- With a lightweight, ultra-thin 1/8" profile
- Even illumination of translucent surfaces from as little as 1/2" behind
- May be field-cut vertically or horizontally, in unique shapes or around obstructions
- Powers easily by daisy chaining with integral push-in connectors or from any square at soldering points provided
- Versatile Mounting Options:
3M-construction adhesive adheres to most surfaces (flat or curved), or open rectangles indicate where it can be stapled through
- Can be installed in either exposed or fully enclosed spaces
- Specially rated for installation in the storage area of a clothes closet


SPECIFICATIONS

- Power Supply:** Remote and electronic Class 2 DC power supply
120-277VAC 50/60Hz input, up to 96W output
- Light Source:** 144 LEDs/sq ft (1 inch pitch)
- Dimming:** Electronic Low Voltage (ELV); electronic 0-10V
- Operating Temp:** -4°F to 104°F (-20°C to 40°C) at relative humidity
- Standards:** 95%UL & CUL Listed for Dry and Damp Locations

Model	Dimension	LED Lumens	Watt	Color Temp	Color
LED	P05 P10	1224	12" x 24"	500 lm/sq ft	5W/sq ft
				1000 lm/sq ft	10W/sq ft
				27 2700K	White
				30 3000K	
				35 3500K	
				40 4000K	
				50 5000K	

LED-P ____ -1224- ____

Example: LED-P10-1224-30



waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760




PIXELS

Configurable LED Light Sheet

WAC LIGHTING

Responsible Lighting®

Required

Type		Model	Input	Output	Max Coverage	Dim
Remote		EN-24100-277-RB2	120-277VAC	24VDC / 96W Class 2	20 sqft (P05) 10 sqft (P10)	0-10V Includes a 6 foot lead wire
Wall Dimmer & Driver		EN-D24100-120-R	120VAC	24VDC / 96W Class 2	20 sqft (P05) 10 sqft (P10)	Integral
Remote		EN-24DC030-UNV-RB2 EN-24DC060-UNV-RB2 EN-24DC096-UNV-RB2	120VAC	24VDC / 30W Class 2 24VDC / 60W Class 2 24VDC / 96W Class 2	6 sqft (P05) 3 sqft (P10) 12 sqft (P05) 6 sqft (P10) 20 sqft (P05) 10 sqft (P10)	ELV/TRIAC

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JULY 24, 2019