

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Paloma LED522 22W Monopoint Luminaire

System Type	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish		
MO	LED522	F 36°	827 2700K - 85	1630	4048	BK Black WT White		
			830 3000K - 85	1695	4218			
			835 3500K - 85	1745	4345			
			840 4000K - 85	1765	4385			
			927 2700K - 90	1355	3375			
			930 3000K - 90	1695	3500			
			827 2700K - 85	1650	5928			
			830 3000K - 85	1625	6177			
			835 3500K - 85	1675	6362			
		N 24°	840 4000K - 85	1690	6422			
			927 2700K - 90	1301	4940			
			930 3000K - 90	1350	5125			
			827 2700K - 85	1590	7622			
			830 3000K - 85	1655	7940			
			835 3500K - 85	1705	8180			
			840 4000K - 85	1720	8257			
			927 2700K - 90	1325	6352			
			930 3000K - 90	1375	6590			
		S 19°						

Example: **MO-LED522F-827-BK**

DESCRIPTION

Paloma is a museum-quality LED luminaire with high performance reflector optics. Available in 12W or 22W options in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture. Monopoint can be ordered with an extension rod (6", 12", 18", 24", 36") to drop the head.

FEATURES

- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Ceiling and wall mountable
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum with cap ring. Clear glass lens included

Power: 22W

Input: 120-277 VAC, 50/60Hz

Dimming: ELV: 100-5%

Light Source: Integrated LED
3 Step Mac Adam Ellipse

Rated Life: 50000 Hours


Finish: Electrostatically Powder Coated White, Black

Operating Temp: -4°F to 104°F (-20°C to 40°C)


Standards: UL, cUL, Damp Location Listed



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Paloma LED522 22W Monopoint Luminaire

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	LENS-20-AMB LENS-20-BLU	<i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i>
	LENS-20-CL	<i>Clear/Frosted Lens</i>	<i>Clear</i>
	LENS-20-SPR	<i>Spread Lens</i>	<i>Spread Lens</i>
	LENS-20-BEL	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>