

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Oculux 2" 11W Open Reflector Round

| Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish |
|----------|-------|------------------|--------|------|-------------------|
| R2BRD-11 | F 45° | 927 2700K - 90 | 890 | 1623 | BN Brushed Nickel |
| | | 930 3000K - 90 | 940 | 1708 | HZWT Haze/White |
| | N 25° | 927 2700K - 90 | 885 | 2809 | WT White |
| | | 930 3000K - 90 | 935 | 2957 | |

Example: **R2BRD-11-F927-BN**

DESCRIPTION

Oculux 2" is an architectural grade recessed downlight with trim, LED light engine, and configurable housing ready to install as an IC-Rated New Construction or Remodel all-in-one unit. Oculux is Energy Star Rated and CEC Title 24 Compliant with Wet Location listing which means it can be installed in a broad range of applications. 35° visual cutoff provides superb glare reduction. Available in Round or Square open reflector and adjustable trim options.

FEATURES

- Cutout 3 1/16"
- Single spot light source
- Ceiling thickness: 1/2" - 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|--|
| Construction: | Die-cast aluminum trim with aluminum heat sink |
| Power: | 11W |
| Input: | 120 VAC, 50/60Hz |
| Dimming: | TRIAC: 100-5%, ELV: 100-5%, 0-10V: 100-5% |
| Light Source: | Integrated LED 3 Step Mac Adam Ellipse |
| Cut Out: | 3 1/16" |
| Finish: | Electrostatically Powder Coated White, Haze/White, Brushed Nickel |
| Ceiling Thickness: | 1/2" - 1" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant, IC, Airtight |



FINISHES



LINE DRAWING

