

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Paloma LED512 9.5W W Track Luminaire

System Type & Voltage	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
WTK-120 VAC WHK-277 VAC	LED512	F 36°	27 2700K - 85	850	2105	BK Black PT Platinum WT White
			30 3000K - 85	885	2195	
			35 3000K - 85	885	2195	
			35 3500K - 85	910	2259	
			40 4000K - 85	920	2282	
			927 2700K - 90	710	1755	
			930 3000K - 90	735	1821	
			27 2700K - 85	685	3152	
			30 3000K - 85	860	3286	
		N 24°	35 3000K - 85	860	3286	
			35 3500K - 85	885	3382	
			40 4000K - 85	895	3417	
			927 2700K - 90	685	2628	
			930 3000K - 90	715	2727	
			S 19°	27 2700K - 85	800	3773
				30 3000K - 85	835	3832
				35 3000K - 85	835	3832
				35 3500K - 85	860	4048
		40 4000K - 85		870	4089	
		927 2700K - 90		670	3145	
		930 3000K - 90		695	3264	

Example: **WHK-LED512F-27-BK**

DESCRIPTION

Paloma is a museum-quality LED luminaire with high-performance reflector optics. Available in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture.

FEATURES

- High Output COB LED
- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS


Construction:	Die-cast aluminum with regressed driver and cap ring. Clear glass lens included.
Power:	9.5W
Input:	120 VAC, 277 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED 3 Step Mac Adam Ellipse
Rated Life:	50000 Hours
Finish:	Electrostatically Powder Coated White, Black, Platinum
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Dry Location Listed



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Paloma LED512 9.5W W Track Luminaire

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	LENS-16-AMB LENS-16-BLU LENS-16-GRN LENS-16-RED	<i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i>
	LENS-16-FR	<i>Clear/Frosted Lens</i>	<i>Frosted</i>
	LENS-16-SPR	<i>Spread Lens</i>	<i>Spread Lens</i>
	LENS-16-BEL	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>
	LENS-16-HCL	<i>Honeycomb Louver</i>	<i>Black</i>