

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Paloma LED512 9.5W W Track Luminaire

System Type & Voltage	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
WTK-120 VAC WHK-277 VAC	LED512	F 36°	27 2700K - 85	850	2105	BK Black PT Platinum WT White
			30 3000K - 85	885	2195	
			35 3000K - 85	885	2195	
			35 3500K - 85	910	2259	
			40 4000K - 85	920	2282	
			927 2700K - 90	710	1755	
			930 3000K - 90	735	1821	
			27 2700K - 85	685	3152	
			30 3000K - 85	860	3286	
		N 24°	35 3000K - 85	860	3286	
			35 3500K - 85	885	3382	
			40 4000K - 85	895	3417	
			927 2700K - 90	685	2628	
			930 3000K - 90	715	2727	
			27 2700K - 85	800	3773	
			30 3000K - 85	835	3832	
			35 3000K - 85	835	3832	
			35 3500K - 85	860	4048	
		S 19°	40 4000K - 85	870	4089	
			927 2700K - 90	670	3145	
			930 3000K - 90	695	3264	

Example: **WHK-LED512F-27-BK**

### DESCRIPTION

Paloma is a museum-quality LED luminaire with high-performance reflector optics. Available in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture.

### FEATURES

- High Output COB LED
- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS


<b>Construction:</b>	Die-cast aluminum with regressed driver and cap ring. Clear glass lens included.
<b>Power:</b>	9.5W
<b>Input:</b>	120 VAC, 277 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10%
<b>Light Source:</b>	Integrated LED 3 Step Mac Adam Ellipse
<b>Rated Life:</b>	50000 Hours
<b>Finish:</b>	Electrostatically Powder Coated White, Black, Platinum
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Dry Location Listed



### FINISHES



### LINE DRAWING



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Paloma LED512 9.5W W Track Luminaire

### ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	<b>LENS-16-AMB</b> <b>LENS-16-BLU</b> <b>LENS-16-GRN</b> <b>LENS-16-RED</b>	<i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i>
	<b>LENS-16-FR</b>	<i>Clear/Frosted Lens</i>	<i>Frosted</i>
	<b>LENS-16-SPR</b>	<i>Spread Lens</i>	<i>Spread Lens</i>
	<b>LENS-16-BEL</b>	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>
	<b>LENS-16-HCL</b>	<i>Honeycomb Louver</i>	<i>Black</i>