

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Paloma LED512 9.5W W Track Luminaire

| System Type & Voltage | Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish | |
|----------------------------|--------|----------------|------------------|---------------|------|-------------------------------------|------|
| WTK-120 VAC WHK-277 VAC | LED512 | F 36° | 27 2700K - 85 | 850 | 2105 | BK Black PT Platinum WT White | |
| | | | 30 3000K - 85 | 885 | 2195 | | |
| | | | 35 3000K - 85 | 885 | 2195 | | |
| | | | 35 3500K - 85 | 910 | 2259 | | |
| | | | 40 4000K - 85 | 920 | 2282 | | |
| | | | 927 2700K - 90 | 710 | 1755 | | |
| | | | 930 3000K - 90 | 735 | 1821 | | |
| | | | N 24° | 27 2700K - 85 | 685 | | 3152 |
| | | | | 30 3000K - 85 | 860 | | 3286 |
| | | 35 3000K - 85 | | 860 | 3286 | | |
| | | 35 3500K - 85 | | 885 | 3382 | | |
| | | 40 4000K - 85 | | 895 | 3417 | | |
| | | 927 2700K - 90 | | 685 | 2628 | | |
| | | 930 3000K - 90 | | 715 | 2727 | | |
| | | S 19° | | 27 2700K - 85 | 800 | 3773 | |
| | | | | 30 3000K - 85 | 835 | 3832 | |
| | | | 35 3000K - 85 | 835 | 3832 | | |
| | | | 35 3500K - 85 | 860 | 4048 | | |
| | | | 40 4000K - 85 | 870 | 4089 | | |
| | | | 927 2700K - 90 | 670 | 3145 | | |
| | | | 930 3000K - 90 | 695 | 3264 | | |

Example: **WHK-LED512F-27-BK**

DESCRIPTION

Paloma is a museum-quality LED luminaire with high-performance reflector optics. Available in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture.

FEATURES

- High Output COB LED
- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS


| | |
|------------------------|--|
| Construction: | Die-cast aluminum with regressed driver and cap ring. Clear glass lens included. |
| Power: | 9.5W |
| Input: | 120 VAC, 277 VAC, 50/60Hz |
| Dimming: | ELV: 100-10% |
| Light Source: | Integrated LED 3 Step Mac Adam Ellipse |
| Rated Life: | 50000 Hours |
| Finish: | Electrostatically Powder Coated White, Black, Platinum |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Dry Location Listed |



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Paloma LED512 9.5W W Track Luminaire

ACCESSORIES

| | <i>Model</i> | <i>Description</i> | <i>Finish</i> |
|---|--|--|---|
|  | LENS-16-AMB LENS-16-BLU LENS-16-GRN LENS-16-RED | <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> | <i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i> |
|  | LENS-16-FR | <i>Clear/Frosted Lens</i> | <i>Frosted</i> |
|  | LENS-16-SPR | <i>Spread Lens</i> | <i>Spread Lens</i> |
|  | LENS-16-BEL | <i>Beam Elongating Lens</i> | <i>Beam Elongating</i> |
|  | LENS-16-HCL | <i>Honeycomb Louver</i> | <i>Black</i> |