

# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## WL-LED120 Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED120 120 VAC	Amber 90 White 90	36 36	BK Black on Aluminum BZ Bronze on Aluminum
WL-LED120F 277 VAC	Amber 90 White 90	36 36	WT White on Aluminum

Example: **WL-LED120-AM-BK**

### DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

### FEATURES

- Louvered design offers shielded illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

### SPECIFICATIONS


<b>Construction:</b>	Die-cast corrosion resistant aluminum alloy
<b>Power:</b>	3W, 3.5W
<b>Input:</b>	120 VAC, 277 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10%
<b>Light Source:</b>	Integrated LED
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x 2"W x 2.5"D
<b>Finish:</b>	Enamel Coated Bronze on Aluminum, Enamel Coated White on Aluminum, Enamel Coated Black on Aluminum
<b>Operating Temp:</b>	-40°F to 104°F (-40°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, IP66, ADA, Title 24 JA8-2016 Compliant

### REPLACEMENT PARTS

- W-4051-120-BZ - LED120 Cover Plate BZ
- W-4051-120-WT - LED120 Cover Plate WT
- W-4051-120-BK - LED120 Cover Plate BK
- 4MT2-S927-BK - 4MT2-N930-BK
- 4MT2-S930-BK - 4MT2-N935-BK
- 4MT2-S935-BK - 4MT2-N940-BK
- 4MT2-S940-BK - 4MT2-F927-BK
- 4MT2-N927-BK - 4MT2-F930-BK



### FINISHES



### LINE DRAWING

