

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Panorama Outdoor Wall Sconce 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
WS-W29718 18"	3000K 90	11.5W	800	245	AL Brushed Aluminum

Example: **WS-W29718-AL**

DESCRIPTION

A breathtaking presentation of light in a vertical or horizontal landscape. Panorama features an edge-lit acrylic diffuser for a unique glare-free illumination with built in water drainage for indoor or outdoor use. Built with solid die-cast aluminum hardware that is weather resistant with a coated brushed aluminum finish. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Edge-lit acrylic diffuser for unique no-glare illumination
- Water drainage designed into fixture
- Weather-resistant powder coated finish
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	36000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, IP65
	Wet Location Listed
Construction:	Aluminum with acrylic diffuser




FINISHES



Brushed
Aluminum

LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Panorama Outdoor Wall Sconce 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
WS-W29724 24"	3000K 90	23.5W	2000	515	AL Brushed Aluminum

Example: **WS-W29724-AL**

DESCRIPTION

A breathtaking presentation of light in a vertical or horizontal landscape. Panorama features an edge-lit acrylic diffuser for a unique glare-free illumination with built in water drainage for indoor or outdoor use. Built with solid die-cast aluminum hardware that is weather resistant with a coated brushed aluminum finish. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Edge-lit acrylic diffuser for unique no-glare illumination
- Water drainage designed into fixture
- Weather-resistant powder coated finish
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	36000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, IP65
	Wet Location Listed
Construction:	Aluminum with acrylic diffuser



FINISHES



Brushed
Aluminum

LINE DRAWING

