# WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

## Paloma LED512

9.5W W Track Luminarie

| System Type & Voltage | Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish |
|---|---|---|---|---|---|---|
| ❍ WTK-120 VAC | ❍ LED512 | ❍ F 36° | ❍ 27 2700K - 85 | 850 | 2105 | ❍ BK Black |
| ❍ WHK-277 VAC | | | ❍ 30 3000K - 85 | 885 | 2195 | ❍ PT Platinum |
| | | | ❍ 35 3000K - 85 | 885 | 2195 | ❍ WT White |
| | | | ❍ 35 3500K - 85 | 910 | 2259 | |
| | | | ❍ 40 4000K - 85 | 920 | 2282 | |
| | | | ❍ 927 2700K - 90 | 710 | 1755 | |
| | | | ❍ 930 3000K - 90 | 735 | 1821 | |
| | | ❍ N 24° | ❍ 27 2700K - 85 | 685 | 3152 | |
| | | | ❍ 30 3000K - 85 | 860 | 3286 | |
| | | | ❍ 35 3000K - 85 | 860 | 3286 | |
| | | | ❍ 35 3500K - 85 | 885 | 3382 | |
| | | | ❍ 40 4000K - 85 | 895 | 3417 | |
| | | | ❍ 927 2700K - 90 | 685 | 2628 | |
| | | | ❍ 930 3000K - 90 | 715 | 2727 | |
| | | ❍ S 19° | ❍ 27 2700K - 85 | 800 | 3773 | |
| | | | ❍ 30 3000K - 85 | 835 | 3832 | |
| | | | ❍ 35 3000K - 85 | 835 | 3832 | |
| | | | ❍ 35 3500K - 85 | 860 | 4048 | |
| | | | ❍ 40 4000K - 85 | 870 | 4089 | |
| | | | ❍ 927 2700K - 90 | 670 | 3145 | |
| | | | ❍ 930 3000K - 90 | 695 | 3264 | |

Example: **WHK-LED512F-27-BK**

### DESCRIPTION

Paloma is a museum-quality LED luminaire with high-performance reflector optics. Available in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture.

### FEATURES

- High Output COB LED
- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS

| | |
|---|---|
| **Construction:** | Die-cast aluminum with regressed driver and cap ring. Clear glass lens included. |
| **Power:** | 9.5W |
| **Input:** | 120 VAC, 277 VAC, 50/60Hz |
| **Dimming:** | ELV: 100-10% |
| **Light Source:** | Integrated LED |
| | 3 Step Mac Adam Ellipse |
| **Rated Life:** | 50000 Hours |
| **Finish:** | Electrostatically Powder Coated White, Black, Platinum |
| **Operating Temp:** | -4°F to 104°F (-20°C to 40°C) |
| **Standards:** | ETL, cETL, Dry Location Listed |

### FINISHES

Black Platinum White

### LINE DRAWING

WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

# Paloma LED512

9.5W W Track Luminarie

## ACCESSORIES

| | *Model* | *Description* | *Finish* |
|---|---|---|---|
| | **LENS-16-AMB**<br>**LENS-16-BLU**<br>**LENS-16-GRN**<br>**LENS-16-RED** | *Colored Lens*<br>*Colored Lens*<br>*Colored Lens*<br>*Colored Lens* | *Amber*<br>*Blue*<br>*Green*<br>*Red* |
|  | **LENS-16-FR** | *Clear/Frosted Lens* | *Frosted* |
| | **LENS-16-SPR** | *Spread Lens* | *Spread Lens* |
| | **LENS-16-BEL** | *Beam Elongating Lens* | *Beam Elongating* |
| | **LENS-16-HCL** | *Honeycomb Louver* | *Black* |