WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Paloma LED522

22W W Track Luminarie

System Type & Voltage	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
❍ WTK-120 VAC	❍ LED522	❍ F 24°	❍ 27 2700K - 85	1630	4048	❍ BK Black
❍ WHK-277 VAC			❍ 30 3000K - 85	1695	4218	❍ PT Platinum
			❍ 35 3000K - 85	1695	4218	❍ WT White
			❍ 35 3500K - 85	1745	4345	
			❍ 40 4000K - 85	1765	4385	
			❍ 927 2700K - 90	1355	3375	
			❍ 930 3000K - 90	1695	3500	
		❍ N 24°	❍ 27 2700K - 85	1650	5928	
			❍ 30 3000K - 85	1625	6177	
			❍ 35 3000K - 85	1625	6177	
			❍ 35 3500K - 85	1675	6362	
			❍ 40 4000K - 85	1690	6422	
			❍ 927 2700K - 90	1301	4940	
			❍ 930 3000K - 90	1350	5125	
		❍ S 19°	❍ 27 2700K - 85	1590	7622	
			❍ 30 3000K - 85	1655	7940	
			❍ 35 3000K - 85	1655	7940	
			❍ 35 3500K - 85	1705	8180	
			❍ 40 4000K - 85	1720	8257	
			❍ 927 2700K - 90	1325	6352	
			❍ 930 3000K - 90	1375	6590	

Example: **WHK-LED522F-27-BK**

DESCRIPTION

Paloma is a museum-quality LED luminaire with high-performance reflector optics. Available in 12W or 22W options in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture. Monopoint can be ordered with an extension rod (6", 12", 18", 24", 36") to drop the head.

FEATURES

- Accommodates 1 filter lens or 1 accessory
- Integral selector to choose between independently controllable track circuits
- 365° horizontal rotation and 180° vertical aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Museum-quality LED luminaire with high performance reflector optics.
Power:	22W
Input:	120 VAC, 277 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
	3 Step Mac Adam Ellipse
Rated Life:	50000 Hours
Finish:	Electrostatically Powder Coated Black, White, Platinum
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Dry Location Listed

FINISHES

Black Platinum White

LINE DRAWING

WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Paloma LED522

22W W Track Luminarie

ACCESSORIES

	Model	*Description*	*Finish*
	LENS-20-AMB **LENS-20-BLU**	*Colored Lens* *Colored Lens*	*Amber* *Blue*
	LENS-20-CL	*Clear/Frosted Lens*	*Clear*
	LENS-20-SPR	*Spread Lens*	*Spread Lens*
	LENS-20-BEL	*Beam Elongating Lens*	*Beam Elongating*