


HR2LEDT109P

2" Tesla™ Pro LED Open Reflector Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round downlight trim with interior open reflector

FEATURES

- 2" aperture
- Energy Star® rated (see below for list of models)
- CEC Title 24 Compliant (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. See table below for Energy Star® and 2013 California Title 24 qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	2013 Title 24	Finish
HR2LEDT109P Open Reflector	N 27°	827 2700K	85	750	2077	Yes	No	BN Brushed Nickel CB Copper Bronze WT White
		927 2700K	90	630	1656	No	No	
		830 3000K	85	810	2250	Yes	No	
		930 3000K	90	700	1871	Yes	Yes	
		835 3500K	85	865	2378	Yes	No	
		840 4000K	85	890	2457	Yes	No	
	F 40°	827 2700K	85	720	1278	Yes	No	
		927 2700K	90	595	1037	Yes	No	
		830 3000K	85	760	1330	Yes	No	
		930 3000K	90	675	1158	Yes	Yes	
		835 3500K	85	830	1476	Yes	No	
		840 4000K	85	860	1519	Yes	No	

HR2LED109P

Example: HR2LED109P927BN

COMPATIBLE HOUSINGS

 See individual housing spec sheets for complete information.

Model	Input	Notes
HR-2LED-H09D-ICA	120V -277V	Ceiling thickness: ½" -¾"
HR-2LED-H09D-ICAC		
HR-2LED-R09D-A	120V -277V	Requires 3" of clearance from insulation on all sides Ceiling thickness: ½" -1"

REPLACEMENT MODULES

Reflectors		
<i>Narrow Flood</i>		SL-REF-BL10-1-N
<i>Flood</i>		SL-REF-BL10-1-F

LED		
<i>2700K</i>	<i>85 CRI</i>	BXRC-27E1000-B-03
<i>2700K</i>	<i>90 CRI</i>	BXRC-27G1000-B-03
<i>3000K</i>	<i>85 CRI</i>	BXRC-30E1000-B-03
<i>3000K</i>	<i>90 CRI</i>	BXRC-30G1000-B-03
<i>3500K</i>	<i>85 CRI</i>	BXRC-35E1000-B-03
<i>4000K</i>	<i>85 CRI</i>	BXRC-40E1000-B-03

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760