

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Paloma LED512 9.5W W Track Luminaire

| System Type & Voltage      | Model  | Beam           | Color Temp & CRI | Lumens        | CBCP | Finish                              |      |
|----------------------------|--------|----------------|------------------|---------------|------|-------------------------------------|------|
| WTK-120 VAC<br>WHK-277 VAC | LED512 | F 36°          | 27 2700K - 85    | 850           | 2105 | BK Black<br>PT Platinum<br>WT White |      |
|                            |        |                | 30 3000K - 85    | 885           | 2195 |                                     |      |
|                            |        |                | 35 3000K - 85    | 885           | 2195 |                                     |      |
|                            |        |                | 35 3500K - 85    | 910           | 2259 |                                     |      |
|                            |        |                | 40 4000K - 85    | 920           | 2282 |                                     |      |
|                            |        |                | 927 2700K - 90   | 710           | 1755 |                                     |      |
|                            |        |                | 930 3000K - 90   | 735           | 1821 |                                     |      |
|                            |        |                | N 24°            | 27 2700K - 85 | 685  |                                     | 3152 |
|                            |        |                |                  | 30 3000K - 85 | 860  |                                     | 3286 |
|                            |        | 35 3000K - 85  |                  | 860           | 3286 |                                     |      |
|                            |        | 35 3500K - 85  |                  | 885           | 3382 |                                     |      |
|                            |        | 40 4000K - 85  |                  | 895           | 3417 |                                     |      |
|                            |        | 927 2700K - 90 |                  | 685           | 2628 |                                     |      |
|                            |        | 930 3000K - 90 |                  | 715           | 2727 |                                     |      |
|                            |        | S 19°          |                  | 27 2700K - 85 | 800  | 3773                                |      |
|                            |        |                |                  | 30 3000K - 85 | 835  | 3832                                |      |
|                            |        |                | 35 3000K - 85    | 835           | 3832 |                                     |      |
|                            |        |                | 35 3500K - 85    | 860           | 4048 |                                     |      |
|                            |        |                | 40 4000K - 85    | 870           | 4089 |                                     |      |
|                            |        |                | 927 2700K - 90   | 670           | 3145 |                                     |      |
|                            |        |                | 930 3000K - 90   | 695           | 3264 |                                     |      |

Example: **WHK-LED512F-27-BK**

### DESCRIPTION

Paloma is a museum-quality LED luminaire with high-performance reflector optics. Available in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture.

### FEATURES

- High Output COB LED
- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS


|                        |  |
|------------------------|--|
| <b>Construction:</b>   | Die-cast aluminum with regressed driver and cap ring. Clear glass lens included. |
| <b>Power:</b>          | 9.5W   |
| <b>Input:</b>          | 120 VAC, 277 VAC, 50/60Hz  |
| <b>Dimming:</b>        | ELV: 100-10%   |
| <b>Light Source:</b>   | Integrated LED<br>3 Step Mac Adam Ellipse  |
| <b>Rated Life:</b>     | 50000 Hours  |
| <b>Finish:</b>         | Electrostatically Powder Coated White, Black, Platinum                           |
| <b>Operating Temp:</b> | -4°F to 104°F (-20°C to 40°C)  |
| <b>Standards:</b>      | ETL, cETL, Dry Location Listed   |



### FINISHES



### LINE DRAWING



Fixture Type: \_\_\_\_\_






Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Paloma LED512 9.5W W Track Luminaire

### ACCESSORIES

|   | <i>Model</i>   | <i>Description</i>   | <i>Finish</i>   |
|---|--|--|---|
|    | <b>LENS-16-AMB</b><br><b>LENS-16-BLU</b><br><b>LENS-16-GRN</b><br><b>LENS-16-RED</b> | <i>Colored Lens</i><br><i>Colored Lens</i><br><i>Colored Lens</i><br><i>Colored Lens</i> | <i>Amber</i><br><i>Blue</i><br><i>Green</i><br><i>Red</i> |
|    | <b>LENS-16-FR</b>  | <i>Clear/Frosted Lens</i>  | <i>Frosted</i>  |
|    | <b>LENS-16-SPR</b>   | <i>Spread Lens</i>   | <i>Spread Lens</i>  |
|  | <b>LENS-16-BEL</b>   | <i>Beam Elongating Lens</i>  | <i>Beam Elongating</i>                                    |
|  | <b>LENS-16-HCL</b>   | <i>Honeycomb Louver</i>  | <i>Black</i>  |