

Installation Instruction

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER

"Note: The installation is for 3, 4, 5 lites, the drawing shown below is for representative only, not to match your new fixture."

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation.
2. Hold Back Plate up against the wall aligning the two holes in the Outlet Box with appropriate slots in the Back Plate. Then while the Back Plate is leveled horizontally, use a pen or pencil to make a mark on the wall at holes located near each end of Back Plate. Set aside the Back Plate and insert Plastic Anchors into the two marks made on the wall.
3. Thread the supply wires and ground wire from Outlet Box through center holes in Back Plate.
4. Attached the Back Plate to Outlet box by using the two Outlet box Screws. If Plastic Anchors were attached to the wall, secure the Back Plate with two Anchors Screws to corresponding holes.
5. Connect the fixture wires to the Outlet Box wires as follows. Connect the White Fixture wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire. Make sure all wire Connectors are secure and do not easily pull off with the slight tug. If there is no Green Ground Wire from the Outlet Box, Connect the Fixture Ground Wire to the Cross Bar with the Green Grounding Screw provided.
6. Once all wires are connected, tuck them carefully into Outlet Box.
7. Place the Fixture Front Plate over the Mounting Screws, so it protrude through the hole in the Back Plate.
8. Thread the Finial onto the Mounting Screws and continue turning until the Fixture Front Plate is snug against Back Plate.
9. Slide Glass Shade and Socket Ring onto Socket, use Socket Wrench to secure Glass Shade and Socket Ring. Install Bulb to Socket
10. Return the power to the Outlet Box and test fixture. Your installation is now complete.

