

CHANDELIER FIXTURE

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Thread the Nipple (18) to Connector(17),then attach Cap(19) through Nipple(18) with Hex nut(20),then place Cap(21) secure with the Finial(22)
2. Screw the Loop(16) to the fixture.
3. Screw the Nipple(8) with the Hex nut(11) and Key washer(10) to the Mounting bar(6).Attach Mounting Bar(6) to the Outlet box(1) by the Mounting screw(7).Screw the Collar loop(13) to the Nipple (8).
4. Link the Chain (15) onto the fixture,slide the Collar ring(14) and Canopy(12) through the chain link the other end of chain onto the Collar loop(13).Weave the fixture wire and ground wire through the chain to the outlet box.
5. Pull out the outlet wire and ground wire from the Outlet box(1).Make wire connections
 - Ribbed wire(w/o marking) from light to White wire(2) from power source.
 - Smooth wire(w/o marking) from light to Black wire(3) from power source.
 - Loop the Ground wire(4) to Mounting bar(6) with a Green screw(9)
6. Put the Glass(24) to the Glass Holder through Socket(23),then secure by Socket ring(26)
- 7.Install bulbs:(bulbs not include)
(Please don't exceed the maximum capacity that recommended on the sockets).

INSTALLATION IS NOW COMPLETED

