

ASSEMBLY AND INSTALLATION INSTRUCTIONS

Item No: 545M/545B/546M/546B

WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.

1. Attach the mounting plate to the outlet box by using two mounting screws.
2. Pull out the outlet wires and house grounding wire from the outlet box. Make wire connections using the wire nuts:
 - The black wire from the light to the black wire from the power source.
 - The white wire from the light to the white wire from the power source.
 - Attach the fixture grounding wire to the mounting plate with the green grounding screw. Then connect it to the house grounding wire with a wire nut.Carefully put the wires back into the outlet box.
3. Attach the back plate to the mounting plate by inserting the round head screws, then secure it with bolt nuts.

CAUTION: With silicone caulking compound, caulk completely around where the back plate meets with the wall surface to prevent water from seeping into the outlet box.
4. Screw the bottom finial and take the frame out.
5. Attach the candle covers to the sockets, and install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.
6. Secure the nipple by using hex nut. Then attach the bottom dome upward to the frame by inserting nipple, then secure it with the bottom finial.
7. Attach the top dome to the frame by inserting the stem, then secure it with the top finial.
8. Turn on the power at the main fuse or circuit breaker box.

